




430 Leo Street _ Dayton, Ohio 45404
 Phone (937) 463-4810 _ Toll Free (866) 878-9283 _ Fax (937) 463-4824

403 West Main Street _ Fountain City, Indiana 47341
 Phone (765) 847-2561 _ Toll Free (800) 331-6040 _ Fax (765) 847-2027

Fleck 2510 Calcite Systems

Neutralizing



2510-TC

Includes the 2510 control valve, 3/4" NPT brass yoke, and polyglass mineral tank.

Units can be customized.

See options section (pg A-34) or call for pricing and availability.



Calcite Systems

Calcite is a granular filter media that dissolves in acidic water to raise the pH level. Reacts slowly to neutralize pH levels with control. Periodic backwashing required.

Calcite Operating Conditions

pH Range: 5-7
 Calcite needs to be added periodically to replace dissolved media.
 Hardness levels increase in neutralizing applications.

Calcite Physical Properties

Color - Near White
 90lbs / cu. ft.
 Mesh Size 16 x 40

2510 Calcite System					
Model #	Media Quantity	Mineral Tank	Service Flow Rate	Backwash Flow Rate	List Price
AFN-10-25	1	10x40 w/dome hole	5.5	4	\$840.00
AFN-15-25	1.5	10x54 w/ dome hole	5.5	4	\$906.00